

PRO-50 TCT | 2-SPEED DRILLING MACHINE





PRO-50 TCT featuring purpose designed motor and 2-speed gear box 320/640 rpm is optimized to provide appropriate speed for work with TCT cutters up to Φ 45 mm and twist drills up to Φ 18 mm. Rigid construction, optimized by means of FEA (finite element analysis) software extends tool life and enables depth of cut up to 75 mm.

Compact design along with innovative smart magnet with reduced weight make it a lightweight machine.

PRO-50 TCT provides maximum holding power on thin materials thanks to Magnetic Field Shape Control (MFSC). The drill protects both the machine and the operator from work on too thin workpiece by means of Magnetic Power Adhesion Control (MPAC). PRO-50 TCT is also equipped with Energy Saving Base (ESB) that uses only 50% of its power when motor is not running.

Features and benefits:

- Compact design with excellent ratio weight/power
- Purpose designed motor
- Motor Speeds 320/640 rpm (under load)
- Spindle equipped with MT2
- Innovative smart magnet with reduced weight
- Rigid design to extend tool life
- Large stroke enables the use of long tools
- Motor cable with additional protective cover
- Magnetic Field Shape Control (MFSC) provides maximum holding power on thin materials
- Magnetic Power Adhesion Control (MPAC) detects adhesive force of electromagnetic base and protects both the machine and the operator from work on too thin workpiece
- Energy Saving Base (ESB) uses only 50% of its power when motor is not running



■ New mid-range drill family at your service

Promotech is introducing new family of drills that are designed for maximum milling/drilling performance.


Customers can choose from 6 models with various tool holders including:

- Thread 1/2"
- Weldon 19,05 mm (3/4")
- Morse Taper #2.

These new drills are optimized for work with HSS cutters, TCT cutters or twist drills.



■ Best practices and new ideas



Increased productivity and extended tool life

The right choice of drilling machine for a specific application can increase process productivity and extend tool life, especially when drilling a large number of holes of the same size.

The design of the new drills is based on well proven electric motor successfully used for many years in the PRO-40 drilling machines.

Most of the components are common between the new models, which allows for flexibility in production, shorter delivery times and immediate response to market demand for specific versions of new drills.

All drills are equipped with smart electromagnetic bases including many advanced systems.

Magnetic power adhesion control module (MPAC) detects adhesive force and protects both the machine and the operator from work on too thin work pieces.

Magnetic field shape control system (MFSC) provides maximum holding power on thin materials.

Energy Saving Base (ESB) uses only 50% of its power when motor is not running. Compact design allows the operator to drill very close to side wall and corners.



Drilling capacity up to 16 mm (0.63")



Out of position drilling



Milling capacity up to 55 mm (2.17")
Depth of cut up to 75 mm (3")



Starting point of milling up to 50 mm (2")
below a level of a drill base

Features and benefits of new mid-range drill family:

- Wide selection of 6 models tailored to certain drilling applications
- Purpose designed motor proven for many years in the PRO-50 drill
- Heavy duty gear boxes optimized to match the appropriate speed of specific tools in use
- Innovative smart magnet with reduced weight
- Compact design with excellent ratio weight / power
- Various tool holders
- Rigid design to extend tool life
- Magnetic Field Shape Control (MFSC)
- Magnetic Power Adhesion Control (MPAC)
- Energy Saving Base (ESB)

Possible tool configurations of PRO-50 TCT



HSS cutters up to Φ 40 mm



TCT cutters up to Φ 45 mm
with AMT2-C19/2-3 arbor D.O.C. up to 75 mm



Starting point of drilling up to 50 mm below
level of a drill base with 100 mm long cutter



Adapter MT2 x 1/2" 20 UNF, Drilling chuck 1/2" 20 UNF
Twist drills up to Φ 16.0 mm (DIN 338)



Adapter MT2 x 1/2" 20 UNF, Quick change drilling chuck 1/2" 20 UNF
Twist drills up to Φ 16.0 mm (DIN 338)



PRO-50 TCT TECHNICAL SPECIFICATION

Motor Speeds (under load)	320/640 rpm
Power	1150 W
Weight	15,5 kg (34.17 lbs)
Max milling capacity TCT/HSS	45/40 mm (1.77"/1.57")
Max drilling capacity	18 mm (0.71")
Stroke	160 mm (6.3")
Max depth of cut	50 mm (2") 75 mm (2.95") option
Voltage	1~ 220-240 V, 50-60 Hz 1~ 110-120 V, 50-60 Hz
MFSC (Magnetic Field Shape Control)	yes
MPAC (Magnetic Power Adhesion Control)	yes
ESB (Energy Saving Base)	yes
Magnetic clamping force	1009 kgf (9900 N)
Magnet base dimensions	84 mm × 168 mm × 48 mm (3.3" × 6.6" × 1.9")
Min. work piece thickness	6 mm (1/4")
Spindle	MT2
Tool holder	19 mm (3/4") Weldon
Product Code 220-240 V, 50-60 Hz	WRT-0742-10-20-00-0
Product Code 110-120 V, 50-60 Hz	WRT-0742-10-10-00-0




Drilling capacity up to 18 mm (0.71")



Milling capacity up to 45 mm (2")
Depth of cut up to 75 mm (3") - option

Standard shipping set:

- Drilling machine
- Plastic box
- Handle (3pcs)
- MT2 arbor with 19 mm (3/4") Weldon tool holder
- Safety strap
- Cooling system
- Protective spring for cooling system hose
- MT2 drift
- 2.5 mm hex wrench
- 5 mm hex wrench
- 5 mm hex wrench with a handle
- 8 mm combination wrench
- Operator's manual



Selected additional accessories:

- PDS-0110-03-00-01-0 Pipe attachment DMP 251 for pipes with diameters of 80-250 mm (3-10")
- PDS-0111-03-00-01-0 Pipe attachment DMP 501 for pipes with diameters of 150-500 mm (6-20")
- TRZ-000008 Adapter MT2 x 1/2" 20 UNF
- UCW-000059 Drilling chuck 1/2" 20 UNF x 1.5-13 mm
- UCW-000061 Drilling chuck 1/2" 20 UNF x 3-16 mm
- UCW-0220-00-00-00-4 Arbor AMT2-C19/2-3 for 75 mm (3") depth cutting
- UKL-0440-16-00-00-0 Pressure cooling system
- PDS-0587-10-00-00-0 Vacuum pad
- AGR-0541-10-20-00-0 (230 V CEE) Vacuum pump
- AGR-0541-10-10-00-0 (115 V UK) Vacuum pump
- ZSP-0587-11-00-00-0 Compressed air ejector



Pipe attachment DMP 251



Pipe attachment DMP 501



Adapter MT2 x 1/2"



Drilling chuck



Arbor AMT2-C19/2-3



Pressure cooling system



Vacuum pad



Vacuum pump



Compressed air ejector



PROMOTECH Sp. z o.o.
ul. Elewatorska 23/1, 15-620 BIAŁYSTOK, POLAND
tel. (+48 85) 678 34 05, fax (+48 85) 662 78 77
marketing@promotech.eu www.promotech.eu

Your local dealer:

